



SCARAP2 :
Rigid and semi-solid shell

Technical Specifications

FIRE RETARDANT

Description :

The Surflex® FIRE RETARDANT safety cap complies with EN 812:2012. It meets the requirements of the EN 812:2012 standard, marked with an 'F', and has been tested for fire retardancy. The cap's fit is reinforced by an elastic band at the nape of the neck.

THE FIRE-RETARDANT IMPACT SHIELD IS TREATED TO DELAY FLAMES AND CONFORMS TO EN 812:2012.

Head protection with ABS shell conforming to EN 812: 2012

'F' marking: ALIEN Certification - EN 812:2012 standard with flame resistance option

Standard 5cm visor



Elastic band Adjustable to keep the cap on the head in all circumstances.

Without ventilation



Ventilated shell: Optimized head ventilation to maximize comfort.



Protective case made of ABS and EVA foam

SURFLEX®

SURFLEX®

Technical Specifications

FIRE RETARDANT

	WITH SHELL	WITHOUT SHELL
REFERENCES		
Navy blue	AIRC02V05RET	AIRC02V05RET-ONLY

GROSS WEIGHT

222 Grammes

SHELL

SCARAP 2 / Rigid and semi-full

SIZE

Adjustable size (56 cm - 64 cm)

MATTER

0% Metal
Shell: ABS (Acrylonitrile butadiene styrene)
Fabric: 100% Polyester (Origin: China)

'F' marking:
ALIENIOR Certification **- Flame Retardant**
EN 812 standard with flame resistance option

MAINTENANCE

Wash at 30°C | Do not bleach | Do not tumble dry | Do not iron | Do not dry clean | Professional cleaning not permitted



CARDBOARD DIMENSIONS

Box of 50 pieces
L 60 cm x l 40 cm x h 40 cm | Poids : 12 kg
Customs code: 65061000

LIFETIME

Shelf life from first use: 36 months
Shelf life from manufacturing: 60 months
Storage life: 36 months



COMPLIANCE

EN 812:2012 standard
EU type examination certificate issued by ALIENOR CERTIFICATION. Notified Body No. 2754. (Download the conformity documents)
- *Compliant with Regulation (EU) 2016/425 on Personal Protective Equipment (PPE) Cat II.*

Warning: The safety cap is not a substitute for a hard hat.

MARKING

Frontal



Embroidery* | Transfer
↔ 85 mm x ↕ 45 mm Max

Embroidery: Fire-retardant thread

Optional add-on

Sides



Embroidery* | Transfer
↔ 60 MM X ↕ 20 MM Max

Embroidery: Fire-retardant thread

Learn more at www.surflex.eu
Click here to access the 2025 CATALOGUE