

SCARAP2 :
Rigid and semi-solid shell

Technical Specifications

CLASSIC

Description :

The EN 812:2012 CLASSIC Surflex® safety cap is **inspired by a baseball cap**. The comfort of this bump cap is enhanced by a sweat-absorbing headband, a shell optimized for **head ventilation**, and an adjustable **elastic band** for a more comfortable fit. An integrated elastic band at the nape of the neck reinforces stability and ensures optimal support during forward or backward movements.



THE BASEBALL CAP BUMP CAP CONFORMS TO EN 812: 2012 STANDARDS

Standard **5cm** visor

Head protection with standardized **ABS shell EN 812:2012**

Available colors



The elastic band at the nape of the neck reinforces the stability of the cap on the head, ensuring optimal support even during forward or backward tilted movements.





Ventilated honeycomb material





Rigid, semi-solid case: SCARAP 2

SURFLEX®

SURFLEX®

Technical Specifications

CLASSIC

REFERENCES

	WITH SHELL	WITHOUT SHELL
Navy blue	BASC02V05	BASC02V05-ONLY
Orange	BASC06V05	BASC06V05-ONLY
Black	BASC01V05	BASC01V05-ONLY

GROSS WEIGHT

183 Grammes

HULL

SCARAP 2 / Rigid and semi-full

SIZE

Adjustable size (56 cm - 64 cm)

MATTER

0% Metal
Shell: ABS (Acrylonitrile butadiene styrene)
Fabric: 100% Polyester (Origin: China)



MAINTENANCE

Wash at 30°C | Do not bleach | Do not tumble dry | Do not iron | Do not dry clean | Professional cleaning not permitted




CARDBOARD DIMENSIONS

Box of 50 pieces
L 60 cm x l 40 cm x h 40 cm | Poids : 10 kg
Customs code: 65061000

LIFETIME

Shelf life from first use: **36 months**
Shelf life from manufacturing**: 60 months**
Storage life**: 36 months**



COMPLIANCE

EN 812:2012 standard
EU type examination certificate issued by ALIENOR CERTIFICATION. Notified Body No. 2754.
(Download the conformity documents)

- *Compliant with Regulation (EU) 2016/425 on Personal Protective Equipment (PPE) Cat II.*

Warning: The safety cap is not a substitute for a hard hat.

MARKING

Frontal



Embroidery
↔ 85 mm x ↕ 50 mm Max

Optional add-on

Frontal



Transfer to the left or right of the seam ↔ 50 mm x ↕ 40 mm Max

Learn more at www.surflex.eu
Click here to access the 2025 CATALOGUE